



With Stokvis Tapes broad range you can solve any task in marking and safety. Slips, trips and falls are one of the single largest causes of major injury in the workplace. Applying an anti-slip product to potentially slippery surfaces not only reduces the risk of employees or visitors slipping and injuring themselves, but can also significantly reduce your exposure to substantial compensation claims.

Safety & Marking Tapes



Anti Slip Tape
Stokvis offers a complete line of pressure sensitive self adhesive anti-slip tapes that are used in a variety of applications.



Line marking tape
Hard wearing PVC film. Produces highly durable, conformable bright lines. Can be removed with minimal time and effort enabling re-marking of demarcation lines. Colours available are red, green, blue, yellow, white, black, red/white and yellow/black.

Easy to use Line marking tape dispenser
Ergonomic dispenser to aid the application of PVC lane marking tapes.



Floor marking tapes
With our wide range of floor identification tapes you can quickly and effectively show any areas of potential danger.



Magnetic tape
Effective identification with this white magnetic film. The vinyl is writable and can be easily moved to another location. Available in several widths.

Barrier tape
Where goods have been quarantined or not yet released to customers, barrier tape provides a visual identification. We can also offer this with text of your choice.



Machine area safety
Visible identification around machinery offers increased safety in the workplace.



Visible identification
Line marking tape helps visible identification across the production area. Available in a number of colours.



Fire equipment
This example shows the clear area in front of fire fighting equipment for ease of access.

Marking in despatch areas
Used when large orders are due to be despatched. This helps to avoid any mistakes in packaging the order.



Tips on tape mounting

Surface Preparation

To guarantee optimum adhesion, surfaces to be bonded must be clean, dry and grease-free.

Anti-adhesive substances on surfaces, such as dust, grease or wax based silicone polishes must be removed before bonding.

Application of Adhesive Tapes

An adhesive tape should stick after application of moderate pressure at ambient temperature (18°C - 25°C). To obtain maximum initial adhesion, even pressure should be applied. The easiest way of achieving this is by finger pressure or using a small hand roller (eg. a seam roller as used for wallpaper hanging). In both cases, firm pressure should be applied along the entire length of the tape. If the adhesive bond or seal is not suitable for the application, please contact us for information on an alternative tape product.



A world of tape solutions



Stokvis Tapes product range:

- Anti-Slip Tape
- Bonding Tape
- Die Cut Tape
- DS Cloth Tape
- DS Foam Tape
- DS Transfer Tape
- Fastfixers
- Film Tape
- Finger Lift Tape
- Fingerprint Tape
- Flame Spray Tape
- Flexo Tape
- Line Marking Tape
- Lithographic Tape
- Magnetic Tape
- Masking Tape
- Medical Tape
- Metal Tapes
- Packaging Tape
- PTFE Tape
- Repealable Tape
- Self-Amalgamating Tape
- Sports Tape
- SS Cloth Tape
- SS Film Tape
- SS Foam Tape
- SS Paper Tape
- Stereo-Mounting Tape
- Teflon Tape
- Tissue Tape
- Velcro®

Stokvis Tapes (UK)

Unit 8, Tring Industrial Estate, Icknield Way
Tring, Hertfordshire, HP23 4JX

Tel: 01442 821700 · Fax: 01442 821722

info@stokvistapes.co.uk
www.stokvistapes.co.uk

an Illinois Tool Works company **ITW**

Effective Marking

STOKVIS TAPES

Effective solutions

