

BA-24-013 TR - Transparent Double Sided PET Tape

Description	This double sided tape consists of a polyester carrier and a solvent based modified acrylic adhesive.
Product properties	It has a very good resistance against UV light, temperatures, chemicals, solvents and humidity. It is highly shear resistant and it is highly durable on metal, varnish and high energy surfaces, and it has a high adhesive durability when attached to low energy surfaces.
Applications	It is used for the attachment of signs, covers, scales, metal and plastic films where high shear strength, adhesion and extreme temperature resistance is required. It is used as a fixing aid in the sail production and for attachment of bars and trims.
Storage and ageing	2 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Carrier	Polyester	
Adhesive	Acrylic modified	
Colour	Transparent	
Liner	Paper brown	
Weather resistant	Yes	
UV resistant	Yes	
Ageing resistant	Yes	
Thickness Carrier	0,012 mm	
Thickness Total	0,13 mm	
Adhesion on stainless steel	30 N/25mm	AFERA 4001
Temperature performance (short time)	180 °C	
Service temperature	-40 - 160 °C	
Application temperature	15 °C	

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.