

CB-12-030 - PVC Coated Cloth Tape

| | |
|--|---|
| Description | This single sided tape consists of a PVC coated non-fraying polyester cloth carrier and a natural rubber adhesive. |
| Product properties | It has a good resistance against abrasion and corrosion, and it has a very good resistance against water. It has a low sulphur and halogen content and a good low temperature performance. It is flexible and very conformable, very strong and robust and it can be written on. It is easy to unwind and to tear. It can be ordered to meet DEF STAN 81/25-3 requirements. |
| Applications | It is a heavy-duty tape used for export packaging and sealing, protecting and strengthening general-purpose applications. It is used for carpet joining, book and spine binding, colour coding and identifications. It is used for joining and splicing, and for technical or demanding applications. |
| Storage and ageing | 2 year shelf life whilst stored in original packaging and ambient room temperature, but usage is recommended within 1 year. Keep out of direct sunlight. |
| Applying tips | All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure. |
| Additional technical properties | Adhesion to backing: 7.5 N/25 mm |

TECHNICAL DATA

| | | |
|------------------------------------|---|------------|
| Carrier | Cloth PVC coated | |
| Adhesive | Rubber natural | |
| Colour | Black, Blue, Brown, Green, Grey, Red, Silver, White, Yellow | |
| Liner | None | |
| Ageing resistant | Yes | |
| Thickness Total | 0,3 mm | |
| Adhesion on stainless steel | 11 N/25mm | AFERA 4001 |
| Tensile strength length | 196 N/25mm | AFERA 4004 |
| Service temperature | 0 - 60 °C | |

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.