

GA-24-100 WH - Double Sided High Performance PE Foam

Description	This double sided tape consists of a closed cell PE foam carrier and a solvent based modified acrylic adhesive.
Product properties	It has a good tack and adhesion, even on rough and difficult surfaces.
Specifications	EU directive 2002/95/EC (RoHS)
Applications	It is used for the installations of spray cast and extruded plastic parts, such as panels, ducts and bars, and Perspex (Plexiglas) mirrors for interior details and displays. It is used as an adhesive medium for hooks, signs, handles and dispensers, and it is used for use in exhibitions and conference mountings.
Storage and ageing	2 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Carrier	PE foam
Adhesive	Acrylic modified
Colour	White
Liner	Paper blue
Weather resistant	Yes
UV resistant	Yes
Ageing resistant	Yes
Density	60 kg/m ³
Thickness Carrier	1 mm
Thickness Total	1,15 mm
Adhesion on stainless steel	18 N/25mm AFERA 4001
Static shear 23°C	2 kg/625mm ² AFERA 4012
Service temperature	-40 - 80 °C
Application temperature	15 °C

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.