

## PA-12-012 - Paper Masking Tape

<b>Description</b>	This single sided tape consists of a crepe paper carrier and a solvent based rubber adhesive.
<b>Product properties</b>	It has good adhesion and is conformable. Good resistance to humidity and relative good resistance to temperature and UV-light. For both indoor and outdoor masking; should be removed within 2 days in outside masking.
<b>Specifications</b>	EU directive 2002/95/EC (RoHS).
<b>Applications</b>	It is used for indoor and outdoor masking in building works, for wall painting, for industrial and automotive masking at medium temperature and for general DIY applications.
<b>Storage and ageing</b>	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

### TECHNICAL DATA

<b>Carrier</b>	Paper	
<b>Adhesive</b>	Rubber	
<b>Liner</b>	None	
<b>Thickness Total</b>	0,125 mm	
<b>Adhesion on stainless steel</b>	4,8 N/25mm	AFERA 4001
<b>Tensile strength length</b>	85 N/25mm	AFERA 4004
<b>Elongation length</b>	9 %	AFERA 4005
<b>Temperature performance (short time)</b>	80 °C	
<b>Service temperature</b>	-20 - 50 °C	

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.