

## TA-21-040 - Adhesive Strip

<b>Description</b>	This transfer tape consists of a solvent free, hot melt synthetic rubber adhesive strip, supplied on a easily removable liner.
<b>Product properties</b>	It is resistant against water and it is solvent free and odourless. It has very good tack and adhesion, and requires no curing time and is non-hardening with a permanent flexibility. It is a clean, easy to use alternative to brush-on adhesives and it can be pre-formed to a choice of sizes. Should not be used where good chemical or UV resistance is required.
<b>Applications</b>	It is used for joining plastic sheeting, filter membranes, damp proofed membranes and bonding lightweight insulation panels, insulation to walls, kick-plates, etc. It is also used for fixing edgings, sheeting, signs and tiles, roof bars on commercial vehicles, carpets and decorative edging, boards and trims, and mounting of lightweight trims and as a temporary "Third hand" fixing.
<b>Processing guidelines</b>	To make the cutting of this tape easier it is recommended dipping the blades/scissors into water just before use.
<b>Storage and ageing</b>	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.
<b>Additional technical properties</b>	Tack rolling ball: 30 mm. Softening point (ring and ball): 85°C.

### TECHNICAL DATA

<b>Carrier</b>	None	
<b>Adhesive</b>	Rubber synthetic	
<b>Colour</b>	Amber	
<b>Liner</b>	Paper silicone coated	
<b>Weather resistant</b>	Yes	
<b>Ageing resistant</b>	Yes	
<b>Thickness Total</b>	0,4 mm	
<b>Dynamic shear</b>	375 N/625mm <sup>2</sup>	ASTM D-1002
<b>Service temperature</b>	0 - 40 °C	
<b>Application temperature</b>	10 °C	

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.