

## XA-25-010 - Double Sided Scrim Tape

<b>Description</b>	This double sided tape consists of a PES/PVA scrim carrier and a pure acrylic dispersion adhesive.
<b>Product properties</b>	It has a good tack and adhesion. Low fogging adhesive. Good resistance to ageing, temperature and plasticizers; no plasticiser migration on most surfaces.
<b>Applications</b>	Because of its low fogging values, it is very suitable for interior car applications.
<b>Storage and ageing</b>	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

### TECHNICAL DATA

<b>Carrier</b>	Scrim	
<b>Adhesive</b>	Acrylic pure	
<b>Liner</b>	Paper silicone coated yellow	
<b>UV resistant</b>	Yes	
<b>Plasticizer resistant</b>	Yes	
<b>Ageing resistant</b>	Yes	
<b>Thickness Total</b>	0,1 mm	
<b>Adhesion on stainless steel</b>	14 N/25mm	AFERA 4001
<b>Service temperature</b>	-40 - 120 °C	

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.